

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau


## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup>:</b> <b>F03B 17/06, 13/12</b>		<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 99/02853</b>
			<b>(43) International Publication Date:</b> 21 January 1999 (21.01.99)
<b>(21) International Application Number:</b> PCT/NO98/00202		<b>(81) Designated States:</b> AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
<b>(22) International Filing Date:</b> 6 July 1998 (06.07.98)			
<b>(30) Priority Data:</b> 973136 7 July 1997 (07.07.97) NO			
<b>(71) Applicant (for all designated States except US):</b> SINVENT AS [NO/NO]; N-7034 Trondheim (NO).			
<b>(72) Inventors; and</b> <b>(75) Inventors/Applicants (for US only):</b> CARSTENS, Torkild [NO/NO]; Aunevegen 16, N-7021 Trondheim (NO). SPIDSØE, Nils [NO/NO]; Øvre Ferstadvæg 14A, N-7022 Trondheim (NO).		<b>Published</b> With international search report. With amended claims. In English translation (filed in Norwegian).	
<b>(74) Agent:</b> CURO AS; P.O. Box 38, N-7094 Lundamo (NO).			

BEST AVAILABLE COPY

**(54) Title:** STREAM TURBINE**(57) Abstract**

Sea turbine with at least one, preferably several water wheels (16), which are connected to an elongated carrier (15) provided to be anchored in a water stream to extend perpendicular to the direction of the water stream. The carrier (15) is symmetrical round a vertical central plane, preferably with a symmetrical wing shaped for use in a bidirectional sea stream. The water wheels (16) are preferably arranged over and under the carrier (15), but can also be arranged between two parallel carriers. The carrier is provided with means to control the buoyancy, e.g. ballast compartments, to be lowered and lifted in the water.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## Stream turbine

The present invention relates to a stream turbine or a stream turbine plant provided to be positioned in straits and other sea areas with one way or two ways tidal stream, to transform kinetic energy of the water stream into a more easily transferable form of energy, e.g. hydraulic or electrical energy. More specifically, the invention relates to a stream turbine as stated in the introductory part of claim 1.

## Background

10 Since ancient times, efforts have been made to exploit kinetic energy of streaming water in rivers and seas. It was early proposed to immerse water wheels from floats or barges, to utilize the rotational energy to operate mills. Propellers arranged on a small electric generator are submersed from leisure boats to generate electrical power.

Several efforts have been made to place permanent stream turbines on the sea bed. From 15 EUR-report 16683 EN published 1996 it is known to place towers with various propellers or other stream turbines in water systems. Such arrangements have been too expensive with current alternative energy costs.

It is also known to use a foil or wing with elongated holding means for propellers extending sideways on one edge, said foils being placed in a water stream. This is intended 20 only for a unidirectional stream.

## Objects

The main purpose of the invention is to provide a stream turbine dimensioned to cover large areas of water streams, which suitably can be manufactured on e.g. ship yards and 25 which easily can be transported to a site of use and be anchored there. It should be submersible and have least possible towering parts. Further, it should be relocizable and be towable to the shore for maintenance and repair. Alternatively, vital parts should be accessible on site for maintenance. It should have reasonable costs and sufficient working life.

30

## Invention

The invention is stated in claim 1. With such a stream turbine or stream turbine plant, large straits and similar sea areas may be covered with energy transformers. It may be sized for large area of stream, though being easily transferable to a site, generally as a barge, the

anchoring means being simple. A stream turbine according to the invention can be effectively module built as module units and be adapted to different sites. It may be kept clear of ship traffic and being adjustable to cover the areas under the ships zone having the largest tidal stream. It can be positioned close to the sea bed.

- 5 A particular advantage of the stream turbine of the invention is its ability to function regardless of sea depth. By suitable anchoring, it is possible to localize the stream turbine according to the invention close to the surface of deep straits and near the bottom of shallow waters.

Additional features of the invention are stated in claims 2-11. Below, the invention is  
10 described more detailed with reference to various embodiments.

#### Example

The invention is illustrated in the drawings, wherein

- Fig. 1 shows a perspective view of a strait with a power plant with a stream turbine  
15 according to the invention in a first embodiment,

Fig. 2 shows a partly sectional side view of the main element of the stream turbine of fig. 1,

Fig. 3-5 shows schematically various alternatives to the embodiment of Fig. 2, while

Fig. 6 shows a partly sectional side view of an alternative stream turbine.

20

- In Fig. 1 is shown a strait 11 between two shores 12 and 13 with a changing stream due to tidal forces. Submerged in the strait 11 is a stream turbine, i.e. a plant 14 for converting the kinetic energy of the moving water. The stream turbine 14 of the example comprises an elongated carrier or beam 15 enclosing converters described below. The carrier 15, which is  
25 shown in section in Fig. 2, has the form of a symmetrical wing, with upper and lower partly flat, partly curved surfaces, which wing is positioned mainly in a horizontal plane.

- Distributed along the carrier 15 of the example is five pairs of water wheels 16. In the example, cylindrical waterwheels, e.g. Darrieus- or Voith-wheels, are used with a vertical axis. To indicate the size, the water wheels of the example may have a diameter of 12 metre  
30 and a length of 12 metre, while the wing can have a height of 4 metre and a width of 25 metre.

In the example of Fig. 1, the carrier 15 is anchored across the strait 11 by two anchoring wires 17 and 18, which are inclined relatively to the direction of the strait 11 to land

anchors 19, 20. The anchors 19 and 20 may suitably be winches operated on the locating and relocating of the stream turbine as described below. By means of the wires 17 and 18 the stream turbine can be immersed to a depth in the strait clear of any ship traffic. It is also possible in shallow waters to operate the winches to lower and lift the carrier 15 cyclically or temporarily to exploit the stream optimal and to allow ship traffic, e.g. by lowering the stream turbine when a ship is passing. It is also possible to arrange stream turbines to provide a ships channel or course and to arrange "stream turbine walls" comprising several modularized stream turbine units, as described below. The distribution of the stream from the surface to deeper layers will govern the design.

10

The carrier 15 comprises one or more energy converters as described below. The converted energy may be transferred by a cable 22 to a power net 23 or through a hydraulic pipe powering a hydraulic motor operating an electrical power generator.

15 In Fig. 2 a section of the stream turbine of Fig. 1 is shown. The carrier 15 has a centrally located engine compartment 31 and a ballast compartment 32, 33 at each side. The engine compartment can be accessible from the upper side for inspection, maintenance and repair through a hatch 34 arranged at the end. This design requires the stream turbine to be lifted to surface position to use the hatch 34. Alternatively it may have the form of a tubular shaft extending like a chimney from the carrier 15 or comprise a lock accessible for a diver.

20

The engine compartment 31 has a flooring 35 carrying a rotational converter 36, e. g. a hydraulic pump or an electric generator. The rotational converter 36 has a shaft extending through the converter to carry two coaxial water wheels 16 with an upper shaft 37 and a lower shaft 38 which are entered into the engine compartment through sealing boxes (not shown). The engine compartment may include equipment needed for converting the rotational energy of the shaft, in a common compartment or in a compartment for each water wheel or pair of water wheels. The engine compartment may have atmospheric pressure or a pressure corresponding to the water pressure.

25

30 The ballast compartments 32, 33 may be emptied in known manner to have a positive buoyancy, e.g. for towing the stream turbine from a building site to a site of operation or for lifting it from a position of use to a position of maintenance. Filling of the ballast

compartments will correspondingly give a negative buoyancy and let the stream turbine sink.

In the example of Fig. 1, the stream turbine has a negative buoyancy and will be suspended  
5 in the pair of wires 17 and 18. An alternative embodiment has anchoring of the wires at the sea bed, requiring positive buoyancy of the stream turbine after positioning, and thus being forced downward by the anchoring wires. This arrangement requires divers or anchoring wires guided on the sea bed, being guided to a winch on the shore.

In Fig. 3 a simplified embodiment of the stream turbine of Fig. 2 is shown, with a water  
10 wheel 42 only on the lower side of the carrier 41, alternatively only on the upper side.

In Fig. 4 an alternative is shown, with the water wheel 43 between two wing shaped carriers 44, 45, the shaft of the water wheel 43 has a link 46 attached to the lower carrier 45 allowing a certain pivoting. In this case, the water wheel 43 may be substantially longer  
15 than in the previous examples.

In Fig. 5 a further alternative is shown, with three rows of water wheels 47, 48, 49 which are arranged stacked with an upper carrier 50 and a lower carrier 51. This arrangement will not allow the entrance into the lower carrier without diving equipment. But this  
20 arrangement will allow the covering of a larger area with one unit. This stream turbine may be towed to the site of usage in a turned down position and then turned 90° in the water by suitably ballasting of the carriers 50 and 51.

The invention can be realized with different configurations of carriers and water wheels, the  
25 water wheels being for axial stream or radial stream. In Fig. 6 an alternative stream turbine is shown, with a water propeller 61 with a hub 62 on a horizontal shaft 63 with a drive gear 64 linked to a vertical drive 65 connected to a power converter 66 in the carrier 67. In all cases an energy converter can be arranged on each shaft, or multiple turbine shafts can operate a common converter shaft (not shown) with only one power converter for each  
30 plant. It is possible to anchor the carrier 15 with wires running up to a sea shore attachment or down to a sea bed anchor. But it is also possible to arrange the stream turbine according to the invention on one or more towers on the sea bed, by controlling lines or anchoring wires.

Additionally is combination with other plants and structures possible. It is e.g. possible to arrange a stream turbin according to the invention on a submersed tunnel bridge, on a submersed water pipe or similar structure.

- 5 The stream turbine according to the invention may be arrange deliberately in the water. Small areas are required on the sea bed or on the surface . In narrow straits a shore based anchoring may be preferred. The carrier should then have a submersed weight which is sufficient to give stability. In open waters the carrier should be anchored at the sea bed, with sufficient buoyancy. The anchoring systems can be based on prior art technology. In  
10 granular masses, poles are submersed with suction pumps or jet dredging. In rock holes are drilled to cement wires being prestressed against rigid discs on the sea bed.

- The stream turbine according to the invention can be unmanned, but accessible for maintenance and repair. It can be floated to the surface to make access through a common  
15 hatch, or by using a shaft or a diver with a lock. It can also be used an inclined tunnel from the sea shore, arranged in or on the shore, with a flexible attachment to the carrier.

- The carrier with water wheels can be premade in a ship yard or other industry and be towed to the site of use. Alternatively it can have its own propulsion, e.g. a motor powering one  
20 or more of the water wheels or a particular propeller, to be moved on its own along a water system. On the site of use, several units can be joined or individually deployed. The deployment may require a step by step maneuver, lowering the carrier by ballasting, being joined to sea shore or sea bed anchoring lines. One or more winches may be used for adjusting the position.

- 25 In reversing streams, which are the most interesting sites, the placing will most easily be done at the tidal current change. By removing, e.g. for repair at shore or overhauling, the described process is reversed.

30

The water wheels with shafts and converting equipment can be made as units to be replaceably arranged in recesses or holes in the carrier, for easy maintenance and repair on

shore. The holes in the carrier can be square or circular. The units can be connected to a common electrical/hydraulic system to transfer the energy to the shore and transfer control signals from the shore.

- 5 When supporting the water wheel shafts in both ends to reduce the shaft tension, one of the carriers, e.g. the lower, can be a simple framework, e.g. with legs to the sea bed.

The water wheels can be arranged mutually close to cover a larger total area than the exposed area.



## Claims:


1. Sea turbine with at least one, preferably several water wheels (16) with vertical or horizontal shafts, which are connected to a carrier (15) provided to be anchored in a water stream to extend perpendicular to the direction of the water stream,  
5 **characterized in**
- the carrier (15) is symmetrical round a vertical central plane,
  - that the water wheels (16) are arranged over and/or under the carrier (15), and
  - that the carrier is provided with means to control the buoyancy, to be lowered and lifted  
10 in the water, being positionable with lines or wires.
2. Sea turbine according to claim 1,  
**characterized in that** the water wheels (43) are arranged between a pair of carriers (44, 45), the link to one of the carriers (45) being pivotable.  
15
3. Sea turbine according to one of the claims 1-2,  
**characterized in that** the carrier (15) is provided with ballast compartments (32, 33) for controlling the buoyancy.
- 20 4. Sea turbine according to one of the claims 1-3,  
**characterized in that** it is provided with anchoring lines (17, 18) at each end for anchoring in a strait or a sea with strong current.
5. Sea turbine according to one of the claims 1-3,  
25 **characterized in that** the carrier is provided to be lowered on one or more towers erected at the sea bed.
6. Sea turbine according to one of the claims 1-5,  
**characterized in that** the carrier (15) is elongated and has pointed edges.  
30
7. Sea turbine according to one of the claims 1-6,  
**characterized in that** the carrier (15) has inside compartments (31) for a common converting shaft or for generators or hydraulic pumps for converting of the energy to a power net.

8. Sea turbine according to claim 7,  
**characterized in that** the inside compartment (31) of the carrier has atmospheric pressure or a pressure corresponding to the water pressure.
- 5 9. Sea turbine according to claim 8,  
**characterized in that** the carrier (15) is provided with a hatch (34), a shaft or a lock, to make the inside compartment (31) accessible.
10. Sea turbine according to one of the claims 1-9,  
10 **characterized in that** the carrier is a completely or partly submerged tubular bridge.
11. Sea turbine according to one of the claims 1-10,  
**characterized in that** it is provided with propulsion means for moving the sea turbine at sea, e.g. a motor for powering one or more water wheels or a propeller.


**AMENDED CLAIMS**

[received by the International Bureau on 07 December 1998 (07.12.98);  
original claims 1-4 amended; remaining claims unchanged (1 page)]


1. Seaturbine with a carrier (15) which is provided to be anchored in a water stream and which is provided with a water wheel (16) with a vertical axis of rotation, said carrier
- 5 (15) having a section lengthwise to the water stream, which is generally symmetrically pointed in both directions, with the axis of the water wheel centrally located, with energy transformers located in the interior of the the carrier to transform the rotational energy of the water wheel to a transferable form of energy, e.g. electrical or hydraulical, **characterized** in that the carrier (15) has the shape of an isometrical wing, with two or
- 10 more water wheels (16) adjacently arranged , which carrier anchored in a stream is arranged horizontally in the water stream, crosswise to the direction of flow, the energy transformers (36) of the separate water wheels being connected in manner known per se to transfer the energy to a place of consumption, particular on shore.
- 15 2. Seaturbine according to claim 1,  
**characterized** in that additionally to a main carrier (44) it comprises a correspondingly designed supplemental carrier (45), the water wheels (43) being arranged between said carriers (44, 45), and the journaling of the water wheels in one of the carriers (45) preferably being twistable.
- 20
3. Sea turbine according to claim 1,  
**characterized** in that the carrier is a completely or partly submerged tubular bridge.
4. Sea turbine according to claim 1 or 2,
- 25 **characterized** in that it is provided with propulsion means for moving the sea turbine at sea, e.g. a motor for powering one or more water wheels or a propeller.




**Fig. 1**




**Fig. 2**




**Fig. 3**



**Fig. 4**



**Fig. 5**



**Fig. 6**

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/NO 98/00202

<b>A. CLASSIFICATION OF SUBJECT MATTER</b>		
IPC6: F03B 17/06, F03B 13/12 According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b>		
Minimum documentation searched (classification system followed by classification symbols)		
IPC6: F03B		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
SE,DK,FI,NO classes as above		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4748808 A (HILL), 7 June 1988 (07.06.88)	1,3,4-9
Y	--	2,10,22
X	US 2730631 A (J.S. DANDINI), 10 January 1956 (10.01.56)	1,7
Y	--	2-6,8-11
X	US 4383182 A (BOWLWY), 10 May 1983 (10.05.83)	1
Y	--	2-11
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C. <input checked="" type="checkbox"/> See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search		Date of mailing of the international search report
19 October 1998		30-10-1998
Name and mailing address of the ISA/ Swedish Patent Office Box 5055, S-102 42 STOCKHOLM Facsimile No. +46 8 666 02 86		Authorized officer  Per.Olof Warnbo Telephone No. +46 8 782 25 00

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/NO 98/00202

## C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 4864152 A (PEDERSEN), 5 Sept 1989 (05.09.89) --	1-11
Y	US 4301377 A (RYDZ), 17 November 1981 (17.11.81) --	1-11
Y	US 3922012 A (HERZ), 25 November 1975 (25.11.75) -- -----	1-11

# INTERNATIONAL SEARCH REPORT

Information on patent family members

27/07/98

International application No.

PCT/NO 98/00202

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
US	4748808	A	07/06/88	AU 600506 B	16/08/90
				AU 7709187 A	29/01/88
				CA 1304272 A	30/06/92
				DE 3777356 A	16/04/92
				EP 0272319 A,B	29/06/88
				JP 63503556 T	22/12/88
				WO 8800297 A	14/01/88
-----					
US	2730631	A	10/01/56	NONE	
-----					
US	4383182	A	10/05/83	NONE	
-----					
US	4864152	A	05/09/89	AU 1058488 A	30/06/88
				DK 155454 B,C	10/04/89
				DK 324087 A	04/06/88
				EP 0292545 A,B	30/11/88
				JP 1501647 T	08/06/89
				SU 1813186 A	30/04/93
				WO 8804362 A	16/06/88
DK 582786 D	00/00/00				
-----					
US	4301377	A	17/11/81	NONE	
-----					
US	3922012	A	25/11/75	NONE	
-----					



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☐ **FADED TEXT OR DRAWING**

☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☒ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**